


**MADE IN
BRITAIN**

SM sievmaster
by farleygreene

Industrial Sieving & Screening Equipment



farleygreene.com

Contents



02 - 03	•	Introduction to Farleygreene			
04 - 05	•	Outline of Sieving Machinery	25	•	700-ST
06 - 07	•	Industries We Serve	26	•	Segregator Range
08 - 11	•	Artisan Range	27 - 30	•	Rota Range
12 - 15	•	Slimline Range	32 - 33	•	Ultrasonic Systems
16 - 18	•	Slimline VS/PS Range	34	•	After Sales Support
19 - 21	•	Slimline Easilift Range	35	•	Process Systems & Equipment
22 - 24	•	Multiscreen Range	36 - 37	•	Choice of Mesh
			38 - 46	•	Technical Drawings





Sieving Partners You Can Trust

We provide sieving and screening solutions to businesses across the world. Our mission is to deliver distinction in our field of expertise, developing flexible modular design, along with clear and concise communication to distribute our product information.

Utilising the latest software, online platforms and manufacturing practices we offer the processes, tools and information that our customers and partners require. This ensures that finding the correctly specified and priced equipment is an easy, composed, courteous and affable experience.

We Understand Your Needs

Farleygreene has the answer to your needs; with our constant dedication to customer service and R&D, our tailored approach exceeds customer expectations. Furthermore, our commitment to maintaining strict working practices has been recognised by being awarded ISO 9001 certification, guaranteeing a high level of quality throughout the process.

Our customers come to us to solve very specific problems:

- > Lack of confidence with existing suppliers
- > Maintain product quality & throughput to meet set production targets
- > Prevent process contamination
- > Maintain a high standard by fitting certified and traceable equipment

Our machines are designed to address all these issues to give you complete peace of mind.



The Benefits We Deliver To Our Customers

Using approved solutions, we work with you to design and build machines to meet your specific requirements; which means your equipment performs as required.

- > Instead of taking a "one size fits all" approach, we adapt our machines to suit your processes. This provides improvements in both efficiency and quality.
- > Our machines can be stripped down without tools which ensures there can be no associated contamination or health and safety issues.
- > The majority of our machines are ATEX approved as standard.
- > We offer a full spares & service package which will ensure years of problem free operation.
- > All equipment is supplied with certified & traceable components as well as relevant documentation to comply with audit procedures.
- > All our machines are manufactured in compliance with both FDA & various other EC regulations such as EC1935/2004.
- > We provide a re-meshing service for existing rings or frames, irrespective of the original supplier.

Our Guarantees To You

While our sieves are designed to give you total confidence that your end-product will meet your quality control specification we go further and offer you two guarantees:

1. While the industry standard is to offer sieving machines with a 12 month warranty, our machines are covered for 24 months against breakdown or malfunction.
2. We guarantee that our machines will perform to the level agreed. If for any reason it fails to perform to the agreed standard, we will either adapt or replace the machine or if necessary refund your money.

Hire & Demo Equipment

We have an extensive fleet of machines available for hire and demonstration or alternatively we can conduct free* in-house trials for you which are filmed and posted to YouTube channel.

Please contact us for current availability as our stock is constantly changing.

*Subject to mesh ring stock, we may need to charge for non-standard fine meshes.

Free One Week Trial

Before you make the decision to buy a new sieve, you may want to check beforehand that it meets your requirements.

We welcome you to trial a machine free for one week in your premises*, with the option of extending this at a reasonable weekly rate.

We will deliver the sieve to you but ask that you arrange for it to be returned to us after the trial. If having read through this brochure you need any further information, please give us a call on +44 (0) 1256 474 547 or email info@farleygreene.com

*depending on global location



Outline of Sieving Machinery

Product sieving is now an essential requirement in nearly all industries. To obtain a quality-controlled end product not only requires diligent constituent choice but careful handling and processing. Removal of any substandard or unwanted matter is therefore a prime requirement.

A SIEVE is a SIEVE, is a SIEVE; a statement often used by the unknowing - but not all sieves are created equal. Choosing a sieve can be a daunting task, not only are there a number of manufacturers purporting to provide the answer to your needs but the choices of differing types, sizes and configurations make the process even more bewildering. Do you choose new

or second hand? Round or square? Buy through an agent or from a manufacturer? Can the supplier support the sale with spares back up, can they support the sale with engineering back up, can they supply all those necessary items to ensure that you can connect your existing or new equipment to the sieve? Is the unit in a hazardous area?

All considerations when making that purchasing decision. Then there is the consideration of price, too expensive? Are you getting value for money? Too cheap? Is the quality of the product suspect? Will it last? It sounds obvious, but the first consideration should be; 'What is the sieve to be used for?'

This fundamental consideration is so often overlooked, but ensuring the requirement is correctly specified will narrow down the choice process. Assistance is always available from Farleygreene for you to evaluate the best options for your application. Screening trials can also be carried out on site or within our test facility to fully prove the process.

Check Sieving

This is the most straightforward arrangement for sieving and in general terms the most popular system in use. Check sieving can be carried out in many differing configurations.

Not all companies require large size sieves, those wishing to separate high cost low volume products very often require small table top sieves. The Artisan range can provide the ideal solution for this. Based upon the need to check sieve and retain oversize product or foreign bodies, these machines are available with enclosed top screen systems that allow the screen and pan to be removed in one. The E400 is a completely modular concept which allows switching between check sieving and grading within one unit.

The most common continuous or batch process option is to position a Sievmaster Slimline unit directly into the flow line of the product, at the beginning or at the end of the production line dependent upon the need. Alternatives include the incorporation of a bag 'rip and tip' station, allowing users the facility to unload sacks of material directly into the process.



Vacuum / Pressure Sieving

Where toxic products or those containing very fine, airborne dust require sieving and there is a danger of contamination to personnel and the surrounding atmosphere, vacuum/pressure sieving has many advantages. However, this type of sieving is not restricted to these product types and can work with any product that can be conveyed pneumatically. A pneumatic conveyline is utilised to enclose the product, with a short flexible pipe connecting it directly to the inlet and outlet of the sieve. The product is drawn or blown through the tube, via under or over pressure, then passes through the mesh and is again transferred from the sieving machine to the receiving hopper or next process. When dealing with problem products this arrangement provides a simple and cost-effective method of ensuring no leakage. The units can be very simply inserted into existing pipework systems with minimal disruption and line reconfiguration. This system can be applied to most types of sieving machine, but airtight connections must be maintained to ensure efficient flow and throughput.



Linear Screeners

As the name suggests, this arrangement moves the product along a rectangular mesh, rather than a circular one. The product is not restricted upon the mesh and it uses gravity as an aid to movement. This type of machine is ideally suited to those products which have a high proportion of oversize material, where it requires de-dusting or de-watering. Especially useful in those areas in the food industry where spices, vegetables or biscuits need separating from unwanted, broken or undersized product. The product travels in a controlled 'bounce' along the screen e.g. in a forward straight motion lifting from the screen thus re-presenting each particle as it travels along. Specially designed parallel screen systems can also aid throughput and separate the most difficult wet and dry products along with soft gel capsules or tablets.



Centrifugal Sifters

Designed to provide users with an efficient, dust tight, high throughput sieving machine, the Sievmaster Rota series gives accurate material screening with continuous fine and coarse discharge. The machine is especially suitable for high volume sieving, lumpy, sticky and dusty products. Product is sieved on a continuous basis and very large quantities can be processed quickly.

Units can be fitted to process lines easily, as the units are non-vibratory, they are 'bolted' within the system via the inlet and outlet flanges. The Sievmaster Rota range can also be configured with a lump breaking aspect, and also features a fully dedicated lump breaker and sieve in one solution option called the Disintegrator. Both these options are perfect for deagglomerating stored powders or kibbling of cinder toffee, biscuits and other confectionary items.



Grading Separators

Where a product flow needs to be separated in to fractions of different sized particles, multi-screened machines should be considered. This is especially effective where the process is continuous, and more space and cost efficient than cascading product from one sieve to the next. Normally, up to three mesh screens can be incorporated in to a single machine, providing an oversize cut, a large cut, a small cut, and a fine cut of the product. These and other units can be fitted with an ultrasonic de-blinding system for difficult powders that may blind the mesh aperture. Rubber balls and sliding collars can also be fitted under the screen as a more economical method of mechanically deblinding the mesh.

Multi-screen machines are available in various sizes starting with 400mm and increasing to 800mm, 1200mm and 1500mm diameters. Modular in their design users can easily switch from single screen with simple fines and oversize, to 3 or 4 cuts.



Ultrasonic Sieving

The use of ultrasonic sieving can, in some instances, provide added benefits when sieving fine powders. The introduction of very high frequency vibration (ultrasonic wave length) to the mesh produces a fluidising effect to the mesh wires, the theory being that the product 'slips' through the mesh more readily than by normal low frequency vibration. This system works well on some products but not all. Tests are important to provide the correct specification. It is especially useful for products such as toner or metals powders used in additive manufacturing environments. Recent internal and site tests have also proven its useful incorporation for high capacity check sieves, as the system provides a constant mesh cleaning function which reduces powder build up on the mesh.





Industries We Serve

Since 1976 Farleygreene have been designing and manufacturing certified sieving solutions to customers from a wide range of industries. We supply sieves to almost every industry sector but in particular to the food and drink, pharmaceutical, chemical, nutraceutical, reclamation and recycling, and additive manufacturing industries.

All machine parts can include full traceability, surface roughness measurements, As Built Drawings and FAT testing documentation.



Food & Drink

Our Sievmaster range has been designed to meet the growing food industry standards (EC1935/2004, ATEX, FDA). We have a large range of options available to meet various throughputs without compromising on strict hygienic requirements.



Pharmaceutical

We have worked with companies such as GSK, TEVA & Pfizer to support the pharmaceutical industry in the supply of contamination free end products. Our standalone vacuum check screener can be easily fitted in existing process lines to safely grade even the most fragile ingredients in hygienic conditions.



Chemical

Our sieving solutions play a key role in the chemical industry to ensure products are validated post process. Through our experience in both liquid and solid processing, our technology has demonstrated its benefits in separating various chemical end products such as solvent based paints.



Nutraceutical

Our experience in the demanding food & pharmaceutical industries has allowed us to expand into the ever growing and highly sought-after nutraceutical industry, where quality plays a critical role in the validation of the end product.



Reclamation & Recycling

Our solutions integrate with factory equipment to ensure optimum separation, reclaim residual product, and help reduce production costs. Our Multiscreen range has been recently updated to increase separation performance on all decks and is available in different diameters to fit various process configurations.



Additive Manufacturing

Our Sievmaster range can be adapted to meet additive manufacturing requirements. Alternatively, our Sievgen range is used specifically for recycling and validating powders throughout the additive process. These units are designed to reduce downtime and fit seamlessly into both R&D and production environments.

Artisan Range

SM 200-S Batch Sieve

Vibratory Sieve for Check Screening Small Batches

The Sievmaster 200-S provides users with a 200mm diameter, all stainless steel check sieve at an affordable price.

This sieve ensures the integrity and quality of ingredients and product to the end user. It is designed to sit directly on top of a container; ingredients can be tipped into the top hopper and check sieved straight through into the container below. It comes with 3 mesh inserts for coarse, medium & fine/liquid applications. Other meshes can be provided as part of a meshed top hopper assembly.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Constructed from FDA compliant materials
- Low maintenance / running costs
- No tool, quick change screens
- Easy clean design, no crevices
- Noise level less than 70 dBA when in use
- All stainless steel contact parts
- The machine plugs into a standard domestic power supply which can be matched to the country of use


TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Liquids

PRODUCT OPTIONS

Machine configurations*

- Top dust cover 
- Top cone meshed 
- Bench mounting kit 

- Collection bin 
- Collection bin cover

*More options available on request

Finishes available

- Standard bead blast finish
- Mirror polish to internal surfaces

CERTIFIED TECHNOLOGY



Artisan Range

SM 500-S

A Smaller Sieve that doesn't Compromise on Throughput and Accuracy

Designed to provide users with the power for fast product throughputs and accurate check sieving. This economically priced sieving machine will suit those needing to sieve products in smaller batches but still requiring a fast, efficient system.

With just a single hand operated band clamp release, the pre-tensioned mesh assembly and the metal detectable gasket are fully removed making this an easy and quick machine to change products and clean. Each machine is supplied ready to use, just connect and go. The mobile stand provides a simple means of manoeuvring from one location to another, ideal when multi-tasking is essential or external cleaning is required.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Check sieve for use in the food, pharmaceutical or chemical industries
- Noise level less than 70 dBA in use
- Can be used for production sieving into tote bins or mixer bowls
- All stainless steel body and contact parts





- Mobile stand for greater flexibility
- Constructed from FDA compliant materials
- No tool, quick change screens
- Easy clean design, no crevices

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa

PRODUCT OPTIONS

Machine configurations*

- Tote bin / container Mounting 
- Addition of underscreen magnet assy 
- Top dust cover 
- Mesh deblinding - mechanical 

- Mesh deblinding - ultrasonic 
- Outlet sleeve 
- Top cone meshed 

Finishes available

- Mirror polish to internal surfaces

CERTIFIED TECHNOLOGY



*More options available on request

Artisan Range

SM E-400-STV

A Modular Check Sieve with Sack Tip Configuration

The E-400 is a highly flexible and efficient solution for lower volume requirements. Primarily aimed at the food and chemicals market, this modular unit can be adapted to meet requirements as they change, or fit different points in a process.

The E-400's mobile design means it can be easily adapted by the user for check screening, grade sieving or low volume sack tipping.

This particular model is the sack tip variant.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- This unit can utilise the GRV components to become a grading unit with no other modifications
- Constructed from FDA compliant materials
- Low maintenance / running costs
- No tool, quick change screens





- Noise level less than 70 dBA when in use
- All stainless steel contact parts
- Mobile support frame
- Easy clean design, no crevices
- Bag cut out and internal sack rest grid




TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Liquids

PRODUCT OPTIONS

Machine configurations*

- Addition of oversize outlet to top gallery c/w oversize control scroll 
- Addition of extra deck with outlet, internal cone, mesh ring, clamp & gasket 
- Standalone dust extractor 
- Operator platform 

- Mesh deblinding - mechanical 
- Addition of underscreen magnet assy 
- Outlet sleeve 

Finishes available

- Mirror polish to internal surfaces

CERTIFIED TECHNOLOGY



*More options available on request

Artisan Range

SM E-400-GRV

A Modular Check Sieve with Grading Configuration

The E-400 is a highly flexible and efficient solution for low volume requirements. Primarily aimed at the food and chemicals market, this modular unit can be adapted to meet requirements as they change, or fit different points in a process.

The E-400's mobile design means it can be easily adapted by the user for check screening, grade sieving or low volume sack tipping.

This particular model is the grading variant.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- This unit can utilise the STV components to become a sack tipping unit with no other modifications
- Constructed from FDA compliant materials
- Low maintenance / running costs
- No tool, quick change screens





- Noise level less than 70 dBA when in use
- All stainless steel contact parts
- Mobile support frame
- Easy clean design, no crevices
- Sieve straight into tote bins, drums or bags



TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Liquids

PRODUCT OPTIONS

Machine configurations*

- Continuous processing of 2 fractions - oversize/fines 
- Continuous processing of 3 fractions - oversize/cut 1/ fines 
- Outlet flexible connection sleeve 
- Addition of underscreen magnet assy 

- Mesh deblinding - mechanical 
- Mesh deblinding - ultrasonic 

*More options available on request

Finishes available

- Mirror polish to internal surfaces

CERTIFIED TECHNOLOGY



Slimline Range

SM 550-FF

Vibratory Check Screener in 550mm Diameter

The 550-FF model can be used as a simple means of check sieving into bins or containers. It is primarily designed to be fed under gravity within new or existing production lines, to screen product into a static weigh bin, big bag, convey line or hopper.

The basic unit will locate within a confined area to provide for retrospective fitting into systems that previously had no sieving equipment. Used with the optional wheeled base assembly, it makes an ideal arrangement to sieve ingredients in small or large batch volumes.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES






- Mobile stands available for greater flexibility, which can be designed to suit installation
- Constructed from FDA compliant materials
- No tool, quick change screens
- Easy clean design, no crevices
- Dust & hose proof IP67
- Noise level less than 70 dBA when in use
- All stainless steel contact parts
- ATEX approved on all sizes as standard
- Can be fitted into sack tipping stations to provide for a dust free, clean operating area
- Vacuum / pressure transfer models available

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders / granular products
- Liquid separation
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Open top version with reduced or extended height top gallery 
- Sack tip entry with Safety grid 
- Inlet diaphragm seal 
- Underscreen magnet assy 
- 304SS tubular handles to clamps 
- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D 

- Cone dispersion type inlet 
- Weirflo type inlet 
- Jacob, BFM and Triclamp inlet / outlet 
- Oversize discharge outlet with weir plate 
- Tubular 'C' type frame 
- Ultrasonic upgrade 
- Safety interlock 

Finishes available

- External mirror polish to top gallery <0.8Ra
- Dressing of all external welds (with standard mirror polish)
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Vivateq/Sublimotion finish - whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Range

SM 950-ST

Vibratory Check Screener in 950mm Diameter

The 950-ST is primarily designed to be fed under gravity within new or existing production lines, to screen product into a static weigh bin, big bag, convey line or hopper.

The 'Slimline' can be located above the inlet to provide an efficient and fast means of ensuring product reliability. The basic unit will locate within a confined area to provide for retrospective fitting into systems that previously had no sieving equipment.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Can be fitted into sack tipping stations to provide for a dust free, clean operating area
- Constructed from FDA compliant materials
- No tool, quick change screens
- Easy clean design, no crevices
- Vacuum / pressure transfer models available
- Noise level less than 70 dBA when in use
- All stainless steel contact parts
- ATEX approved on all sizes as standard
- Dust & hose proof IP67





TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders / granular products
- Liquid separation
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D 
- 304SS tubular handles to clamps 
- Easy clean drawer magnet assy 
- Cone dispersion type inlet 
- Weirflo type inlet 
- Vision port 

- Jacob, BFM and Triclamp inlet / outlet 
- Oversize discharge outlet with weir plate 
- Support frame assy 
- Collection bin 
- Ultrasonic upgrade 
- Safety interlock 

Finishes available

- External mirror polish to top gallery < 0.8Ra
- Dressing of all external welds (with standard mirror polish)
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Vivateq/Sublimotion finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY




Slimline Range

SM 1250-ST

Vibratory Check Screener in 1250mm diameter

The 1250-ST is primarily designed to be fed under gravity within new or existing production lines, to screen product into a static weigh bin, big bag, convey line or hopper.

This larger unit is technically similar to the SM550/950 models but are designed for very high throughput requirements and have some small design changes due to the size and weight of the components. Maximum consideration is given in the design to ensure these large units can be stripped down by operators.



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

INDUSTRIES

FEATURES

- Support frames available, which can be designed to suit installation
- Constructed from FDA compliant materials
- No tool, quick change screens
- Easy clean design, no crevices
- Dust & hose proof IP67

- Noise level less than 70 dBA when in use
- All stainless steel contact parts
- ATEX approved on all sizes as standard
- Vacuum / pressure transfer models available

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders/ granular products
- Liquid separation
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D 
- 304SS tubular handles to clamps 
- Easy clean drawer magnet assy 
- Cone dispersion type inlet 
- Weirflo type inlet 
- Vision port 

- Jacob, BFM and Triclamp outlet end 
- Jacob, BFM and Triclamp inlet end 
- Oversize discharge outlet with weir plate 
- Support frame assy 
- Collection bin 
- Ultrasonic upgrade 
- Safety interlock 

Finishes available

- External mirror polish to top gallery < 0.8Ra
- Dressing of all external welds (with standard mirror polish)
- Pharmaceutical mirror polish < 0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimotion finish - whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Range

SM 1550-ST

Vibratory Check Screener in 1550mm Diameter

The 1550-ST is primarily designed to be fed under gravity within new or existing production lines, to screen product into a static weigh bin, big bag, convey line or hopper.

This larger unit is technically similar to the SM550/950 models but are designed for very high throughput requirements and have some small design changes due to the size and weight of the components. Maximum consideration is given in the design to ensure these large units can be stripped down by operators.



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

INDUSTRIES

FEATURES

- Support frames available, which can be designed to suit installation
- Constructed from FDA compliant materials
- No tool, quick change screens
- Easy clean design, no crevices
- Noise level less than 70 dBA when in use






- All stainless steel contact parts
- ATEX approved on all sizes as standard
- Vacuum / pressure transfer models available







TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Most powders/ granular products
- Liquid separation
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D 
- 304SS tubular handles to clamps 
- Easy clean drawer magnet assy 
- Cone dispersion type inlet 
- Weirflo type inlet 
- Vision port 

- Jacob, BFM and Triclamp outlet end 
- Jacob, BFM and Triclamp inlet end 
- Oversize discharge outlet with weir plate 
- Support frame assy 
- Collection bin 
- Ultrasonic upgrade 
- Safety interlock 

Finishes available

- External mirror polish to top gallery < 0.8Ra
- Dressing of all external welds (with standard mirror polish)
- Pharmaceutical mirror polish < 0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimotion finish - whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Range

SM 550-VS

Vibratory Check Screener for Pneumatic Conveying

Wherever loose powders are sieved, airborne dust being generated is nearly always a problem. It is unpleasant within the working environment, and more importantly hazardous to health. The SM 550-VS has been designed to overcome this issue and provide a means of transferring and sieving product from one area to another in a single operation.

This model is vacuum only. Pressure transfer system available with larger models.



INDUSTRIES

- Food & Drink
- Pharmaceutical
- Chemical
- Nutraceutical
- Reclamation & Recycling
- Additive Manufacturing

FEATURES

- Enclosed system removing the issue of airborne dust
- ATEX approved on all sizes as standard
- Production sieving into conveyor, mixer or bagging machines
- Constructed from FDA compliant materials
- Dust & hose proof IP67
- Inlets/outlets sized to suit new or existing convey lines
- Mobile stands for greater flexibility
- No tool, quick change screens
- Easy clean design, no crevices
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D
- 304SS tubular handles to clamps
- Addition of underscreen magnet assy
- Price reduction option
- Inlet powder entry flow type
- Oversize outlet c/w connection to manual butterfly valve

- Oversize outlet c/w connection to pneumatically actuated butterfly valve
- Fluidisation to funnel cone
- Air bleed valve after outlet
- Ultrasonic upgrade
- Collection bin 35L
- Safety interlock

Finishes available

- Dressing of all external welds (with mirror polish)
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimation finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Range

SM 950-VS/PS

Vibratory Check Screener for Pneumatic Conveying

Wherever loose powders are sieved, airborne dust being generated is nearly always a problem. It is unpleasant within the working environment, and more importantly hazardous to health. The SM 950-VS has been designed to overcome this issue and provide a means of transferring and sieving product from one area to another in a single operation.



INDUSTRIES

- Food & Drink
- Pharmaceutical
- Chemical
- Nutraceutical
- Reclamation & Recycling
- Additive Manufacturing

FEATURES

- Enclosed system removing the issue of airborne dust
- ATEX approved on all sizes as standard
- Production sieving into conveyor, mixer or bagging machines
- Constructed from FDA compliant materials
- Dust & hose proof IP67
- Inlets/outlets sized to suit new or existing convey lines
- Mobile stands for greater flexibility
- No tool, quick change screens
- Easy clean design, no crevices
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D
- 304SS tubular handles to clamps
- Inlet powder entry flow type
- Safety interlock
- Fluidisation to funnel cone

- Oversize outlet c/w connection to manual butterfly valve
- Oversize outlet c/w connection to pneumatically actuated butterfly valve
- Air bleed valve after outlet
- Ultrasonic upgrade
- Collection bin

Finishes available

- Dressing of all external welds (with mirror polish)
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimation finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



*More options available on request

Slimline Range

SM 1250-VS/PS

Vibratory Check Screener for Pneumatic Conveying

Wherever loose powders are sieved, airborne dust being generated is nearly always a problem. It is unpleasant within the working environment, and more importantly hazardous to health. The SM 1250-VS has been designed to overcome this issue and provide a means of transferring and sieving product from one area to another in a single operation.

Vacuum and pressure model shown opposite.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES







- Enclosed system removing the issue of airborne dust
- ATEX approved on all sizes as standard
- Production sieving into conveyor, mixer or bagging machines
- Constructed from FDA compliant materials
- Dust & hose proof IP67
- Inlets/outlets sized to suit new or existing convey lines
- Mobile stands for greater flexibility
- No tool, quick change screens
- Easy clean design, no crevices
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Upgrade to - Internal: ATEX 20 II 1D External: ATEX 22 II 3D 
- 304SS tubular handles to clamps 
- Inlet powder entry flow type 
- Safety interlock 
- Fluidisation to funnel cones 
- x2 vision ports as standard 

- Oversize outlet c/w connection to manual butterfly valve 
- Oversize outlet c/w connection to pneumatically actuated butterfly valve 
- Air bleed valve after outlet 
- Ultrasonic upgrade 
- Collection bin 

Finishes available

- Dressing of all external welds (with mirror polish)
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Viwatec/Sublimation finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Easilift Range

SM 550-ESL

Sack Tipping Check Screener

The Sievmaster Easilift sack tipping station has been designed with a Pneumatically assisted hood for easy access to the sieve without heavy lifting. Used together with the Slimline vibratory check screener, this machine features an inclined sack rest table for low level bag tipping.

Standard 25kg bags of product can be dispensed directly in to the sieve for check screening into containers, static weigh bins, convey systems or mixers.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Connection to vacuum transfer systems or any other convey equipment
- Pneumatically assisted hood - no heavy lifting or awkward sleeve connections
- Standard 900mm ergonomic sack tipping height
- Low care to High care transfer systems available
- Integrated dust extraction and filtration units
- Inlet enclosure doors
- No tool, quick change screens
- Easy clean design, no crevices
- Dust & hose proof IP67
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Removal of front door 
- Connection to vacuum transfer system 
- Addition of underscreen magnet assy 
- 304SS tubular handles to clamps 
- Safety interlock on sieve & dusthood 
- Fluidisation to funnel cone 
- Dusthood assy in 316SS 
- Support frame in 316SS 
- Dust suppression cover 
- Local dust extraction - Electric / vacuum 
- Step with platform 
- Ultrasonic upgrade 

Finishes available

- Dressing of all external welds
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- WIP / CIP cleaning to dusthood and sieve
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Easilift Range SM 950-ESL

Sack Tipping Check Screener for Large Volume Requirements

The Sievmaster Easilift sack tipping station has been designed with a Pneumatically assisted hood for easy access to the sieve without heavy lifting. Used together with the Slimline vibratory check screener, this machine features an inclined sack rest table for low level bag tipping.

Standard 25kg bags of product can be dispensed directly in to the sieve for check screening into containers, static weigh bins, convey systems or mixers.



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Connection to vacuum transfer systems or any other convey equipment
- Pneumatically assisted hood - no heavy lifting or awkward sleeve connections
- Low care to High care transfer systems available
- Standard 900mm ergonomic sack tipping height
- Integrated dust extraction and filtration units
- Inlet enclosure doors
- No tool, quick change screens
- Easy clean design, no crevices
- Dust & hose proof IP67
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Removal of front door 
- Connection to vacuum transfer system 
- Easy clean drawer magnet assy 
- 304SS tubular handles to clamps 
- Safety interlock on sieve & dusthood 
- Fluidisation to funnel cone 
- Dusthood assy in 316SS 
- Support frame in 316SS 
- Dust suppression cover 
- Local dust extraction - Electric / vacuum 
- Step with platform 
- Ultrasonic upgrade 

Finishes available

- Dressing of all external welds
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- WIP / CIP cleaning to dusthood and sieve
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Easilift Range SM 550-ESL-ULTRA

Ultra Hygienic Sack Tipping Check Screener

The Sievmaster Easilift Ultra sack tip station has been designed primarily for the food industry where hygiene is of prime importance. Similar to the standard Easilift, the Ultra version also features a pneumatically assisted dust hood but is completely crevice free. A fold out sack table ensures a hygiene barrier between sanitary and non-sanitary environments, and a side mount motor improves user access. Used in combination with the Slimline check screener, this machine can process up to 25kg worth of powder at once, dispensing into containers, static weigh bins or incorporated into convey systems.



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES










- Reduced frame area for greater outlet access
- Integrated dust extraction ready
- Pneumatically assisted hood - no heavy lifting or awkward sleeve connections
- Quick release door catch and interlock switch ready
- Constructed from FDA compliant materials
- Inlet door seal for dust suppression and wet in place
- No tool, quick change screens
- Dust & hose proof IP67
- Crevice free for easy cleaning

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Removal of front door 
- Connection to vacuum transfer system 
- Addition of underscreen magnet assy 
- 304SS tubular handles to clamps 
- Safety interlock 
- Fluidisation to funnel cone 
- Dusthood assy in 316SS 
- Support frame in 316SS 
- Dust suppression cover 
- Local dust extraction - Electric / vacuum 
- Step with platform 
- Ultrasonic upgrade 

Finishes available

- Dressing of all external welds
- Pharma mirror polish < 0.25Ra & dressing of all external welds
- Passivation after polish
- WIP / CIP cleaning to dusthood and sieve
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Multiscreen Range

SM 800

Vibratory Sieve for Grading and Separating

Separate, grade, and sort nearly all types of materials into different sizes, using the Multiscreen vibratory sieve. Its weight configuration technology controls the amount of time product is sat on mesh screens, and the debinding system eliminates clogging for a consistent throughput and mesh longevity. The Multiscreen can be used in all types of industries and environments and features a quick change mesh system that allows for easy mesh changes and cleaning.

800mm diameter screen for medium throughput applications.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Specially designed frames and extended height bases
- Scroll system for maximum screening efficiency
- Separation of milled or ground products in up to 4 grades in one pass
- Screening of fine powders (e.g. toner powder, metal powders)







- Grading of kibbled or "disintegrated" products
- Constructed from FDA compliant materials
- Quick change bonded screens
- Easy clean design, no crevices
- Quality assured graded end product
- Noise level less than 70 dBA when in use






TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Continuous processing of 2 fractions - oversize/fines 
- Continuous processing of 3 fractions - oversize/cut 1/fines 
- Continuous processing of 4 fractions - oversize/cut 1/cut 2 / fines 
- ATEX upgrade 
- Enclosed top cover 
- Vision port 

- Intermediate deck dwell control quarter scroll 
- Dwell control full scroll 
- Mesh debinding - mechanical 
- Mesh debinding - ultrasonic 
- Mobile base assy 
- Hygiene base assy 
- Hygiene vibro body & suspension 

Finishes available

- Internal mirror polish to galleries (standard < 0.8Ra)
- Dressing of all internal / external welds
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimotion finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Multiscreen Range

SM 1200

Vibratory Sieve for Grading and Separating

Separate, grade, and sort nearly all types of materials into different sizes, using the Multiscreen vibratory sieve. Its weight configuration technology controls the amount of time product is sat on mesh screens, and the debinding system eliminates clogging for a consistent throughput and mesh longevity. The Multiscreen can be used in all types of industries and environments and features a quick change mesh system that allows for easy mesh changes and cleaning.

1200mm diameter screen for high throughput applications.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Specially designed frames and extended height bases
- Scroll system for maximum screening efficiency
- Separation of milled or ground products in up to 4 grades in one pass
- Screening of fine powders (e.g. toner powder, metal powders)







- Grading of kibbled or "disintegrated" products
- Constructed from FDA compliant materials
- Quick change bonded screens
- Easy clean design, no crevices
- Quality assured graded end product
- Noise level less than 70 dBA when in use








TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Continuous processing of 2 fractions - oversize / fines 
- Continuous processing of 3 fractions - oversize / cut 1 / fines 
- Continuous processing of 4 fractions - oversize /cut 1/ cut 2 / fines 
- ATEX upgrade 
- Enclosed top cover 
- Vision port 

- Intermediate deck dwell control quarter scroll 
- Dwell control full scroll 
- Mesh debinding - mechanical 
- Mesh debinding - ultrasonic 
- Mobile base assy 
- Hygiene base assy 
- Hygiene vibro body & suspension 

Finishes available

- Internal mirror polish to galleries (standard < 0.8Ra)
- Dressing of all internal / external welds
- Pharmaceutical mirror polish <0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq / Sublimotion finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



Slimline Multiscreen Range

SM 1500

Vibratory Sieve for Grading and Separating

Separate, grade, and sort nearly all types of materials into different sizes, using the Multiscreen vibratory sieve. Its weight configuration technology controls the amount of time product is sat on mesh screens, and the deblinding system eliminates clogging for a consistent throughput and mesh longevity. The Multiscreen can be used in all types of industries and environments and features a quick change mesh system that allows for easy mesh changes and cleaning.



1500mm diameter screen for very high throughput applications.

INDUSTRIES	Food & Drink	Pharmaceutical	Chemical	Nutriceutical	Reclamation & Recycling	Additive Manufacturing
------------	--------------	----------------	----------	---------------	-------------------------	------------------------

FEATURES

- Specially designed frames and extended height bases
- Scroll system for maximum screening efficiency
- Separation of milled or ground products in up to 4 grades in one pass
- Screening of fine powders (e.g. toner powder, metal powders)
- Grading of kibbled or "disintegrated" products
- Constructed from FDA compliant materials
- Quick change bonded screens
- Easy clean design, no crevices
- Quality assured graded end product
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- Continuous processing of 2 fractions - oversize / fines
- Continuous processing of 3 fractions - oversize / cut 1 / fines
- Continuous processing of 4 fractions - oversize/cut 1/cut 2 / fines
- ATEX upgrade
- Enclosed top cover
- Vision port

- Intermediate deck dwell control quarter scroll
- Dwell control full scroll
- Mesh deblinding - mechanical
- Mesh deblinding - ultrasonic
- Hygiene base assy
- Hygiene vibro body & suspension

Finishes available

- Internal mirror polish to galleries (standard < 0.8Ra)
- Dressing of all internal/external welds
- Pharmaceutical mirror polish < 0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimotion finish -whole machine
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



*More options available on request

SM 700-ST

Heavy Duty Vibratory Sieve for Check Screening & Grading

The Sievmaster 700-ST uses powerful vibration to separate material on a continuous basis, and quick-change mesh screens mean minimum interruption between batches. The smooth, clean design means there are no exposed rotating parts, and a fully sealed drive system means it can be used in the most arduous environments. Ideal for areas where maximum usage is required and where high pressure hosing down might be normal. Fast, efficient sieving contained within a robust unit.



INDUSTRIES	Food & Drink	Pharmaceutical	Chemical	Nutriceutical	Reclamation & Recycling	Additive Manufacturing
------------	--------------	----------------	----------	---------------	-------------------------	------------------------

FEATURES

- Scroll system for maximum screening efficiency
- High speed version for fine powders
- Check sieving and grading under FIBC/IBC blender discharging systems
- Product sieving into sacks or containers
- Separates oversize from fine material continuously
- Constructed from FDA compliant materials
- No tool, quick change screens
- Easy clean design, no crevices
- Dust & hose proof IP67
- Noise level less than 70 dBA when in use

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Pharmaceutical powders
- Most powders/ granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Wet or dry applications

PRODUCT OPTIONS

Machine configurations*

- ATEX upgrade
- Reduced height top gallery
- Extended height top gallery
- Enclosed top cover
- Addition of underscreen magnet assy
- 304SS tubular handles to clamps

- Dwell control quarter scroll
- Dwell control full scroll
- Vision port
- Mesh deblinding - ultrasonic
- Safety interlock
- High speed motor

Finishes available

- Dressing of all internal/external welds (with standard mirror polish)
- Pharmaceutical mirror polish < 0.25Ra & dressing of all external welds
- Passivation after polish
- Viwateq/Sublimotion finish
- Upgrade from earth clips to external direct mesh earthing system

CERTIFIED TECHNOLOGY



*More options available on request

Segregator Range SM 42 & 53

Linear Vibratory Screener

The Sievmaster Segregator has a large screen area designed to move wet or dry product in a linear motion. It is ideally suited to light fragile products with low bulk densities.

A 'Hygiene' series is also available, developed especially for the food industry and manufactured entirely from stainless steel. These easy clean units can be supplied upon wheels for mobility or feet for static installations. The range is available with variations to provide up to 3 separations, with a wide choice of sieving aids for problem materials. Each unit is made to order to the customers exact process needs.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Available in 1250 mm long x 650 mm wide and 1550 mm long x 920 mm wide mesh frame sizes
- Easy clean design, no crevices
- Dust & hose proof
- Constructed from FDA compliant materials
- Quick change bonded screens
- Low maintenance/running costs
- Noise level less than 70 dBA in use
- Your product quality maintained
- Sieve and convey in one action
- Full validation packages for food/pharma

TYPICAL MATERIALS



- Wet or dry applications
- De-dusting & de-watering
- Liquid separation
- Almost any powder or granulated material
- Biscuits
- Confectionary
- Seeds
- Liquid separation
- Tablets & capsules

PRODUCT OPTIONS

Machine configurations*

- ATEX upgrade 
- FDA/EC upgrade 
- Ultrasonic upgrade 

*More options available on request

- Mesh deblinding - mechanical 
- Jacob or BFM inlet/outlet/oversize 
- Other made to order options available

Finishes available

- Mirror polish to internal surfaces
- Other finishes available depending on application requirements

CERTIFIED TECHNOLOGY



Rota Range

SM R200-ST & R200-ST-LB

Centrifugal Check Sifter with Fixed Drive Shaft Supported at Both Ends

The Rota 200-ST is the mainstay of and introductory model to the Sievmaster Rota Series. The drive shaft is supported by bearings at both ends, one of which is removed with the end door assembly to change the meshes and for cleaning. The Rota 200-ST-LB is nearly identical to the Rota 200-ST but comes with the addition of a larger sized inlet, extending the auger by 250mm and changing the auger flight to a toothed profile. The purpose of this is to improve the ability of the auger to handle product that's more difficult to break down.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Inlets and outlets are designed with standardised flanges but can be supplied with adaptors to suit any connection
- All motors and electrical items are IP55 rated, machine can be washed down without fear of ingress
- All doors and access points are fitted with magnetic interlock switches
- Dust tight design, non-vibratory
- Low maintenance/running costs
- Quick change screens with an easy clean design
- Constructed from FDA compliant materials and without crevices
- Pneumatic conveying system integration

PRODUCT OPTIONS

Machine configurations*

- ATEX upgrade 
- Wedgewire mesh basket 
- Bonded mesh basket 
- Inlet transition piece 
- Fines transition piece 
- Oversize transition piece 

- Easy clean magnet assy to fines 
- Support frame static or mobile 
- Oversize collection barrel 
- Fill level alarm 
- Oversize outlet control 

*More options available on request

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Most non-friable powders/granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Agrochemicals/fertiliser

Finishes available

- Mirror polish to internal stainless parts (standard < 0.8Ra)
- Dressing of all internal/external welds - all stainless parts
- Pharma mirror polish < 0.25Ra & dressing of all internal/external welds - all stainless parts
- Passivation after polish to all stainless parts
- Viwateq/Sublimation finish to all stainless parts
- Electropolish to all stainless parts

CERTIFIED TECHNOLOGY



Rota Range SM R200-C

Centrifugal Check Sifter with Cantilever Drive Shaft Support at Drive End

The Rota 200-C does not have a bearing at each end of the auger drive shaft, but instead has a cantilevered auger and paddle assembly. This makes it significantly quicker and easier to remove the mesh basket and auger paddle assemblies for cleaning. It also allows the oversize weir plate to be completely closed off ensuring all product will pass through the mesh.



INDUSTRIES

- Food & Drink
- Pharmaceutical
- Chemical
- Nutraceutical
- Reclamation & Recycling
- Additive Manufacturing

FEATURES

- Inlets and outlets are designed with standardised flanges but can be supplied with adaptors to suit any connection
- All motors and electrical items are IP55 rated, machine can be washed down without fear of ingress
- All doors and access points are fitted with magnetic interlock switches
- Pneumatic conveying system integration
- Dust tight design, non-vibratory
- Low maintenance/running costs
- Quick change screens with an easy clean design
- Ø184mm inlet, a Ø200mm fines outlet and a Ø100mm oversize outlet
- Constructed from FDA compliant materials and without crevices

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Most non-friable powders/granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Agrochemicals/fertiliser

PRODUCT OPTIONS

Machine configurations*

- ATEX upgrade
- Wedgewire mesh basket
- Bonded mesh basket
- Inlet transition piece
- Easy clean magnet assy to fines

- Support frame static or mobile
- Oversize collection barrel
- Fill level alarm
- Oversize outlet control

*More options available on request

Finishes available

- Mirror polish to internal stainless parts (standard < 0.8Ra)
- Dressing of all internal/external welds - all stainless parts
- Pharma mirror polish < 0.25Ra & dressing of all internal/external welds - all stainless parts
- Passivation after polish to all stainless parts
- Vivateq/Sublimotion finish to all stainless parts
- Electropolish to all stainless parts

CERTIFIED TECHNOLOGY



Rota Range SM R200-Disintegrader

Centrifugal Lump Breaker with Fixed Drive Shaft Supported at Both Ends

The Rota Disintegrader also shares a significant number of its characteristics with the R200-ST. Whereas the R200-ST-LB improves on the deagglomeration capability of the R200-ST, the R200-DIST is a dedicated lump breaker. The inlet is replaced with a large wide-throated hopper, designed to be filled with product whilst the auger is inactive. After the unit has been loaded in "safe mode" the processing of the material will begin with no risk to the operator.



INDUSTRIES

- Food & Drink
- Pharmaceutical
- Chemical
- Nutraceutical
- Reclamation & Recycling
- Additive Manufacturing

FEATURES

- Outlets are designed with standardised flanges but can be supplied with adaptors to suit any connection
- All motors and electrical items are IP55 rated, machine can be washed down without fear of ingress
- All doors and access points are fitted with magnetic interlock switches
- 100L hopper volume with 900mm ergonomic sack tip height and hinged, self-lifting top lid to cover
- Automatic start up on lid closure
- Fines outlet measures 412mm x 600 mm, oversize outlet measures 412mm x 149 mm
- Pneumatic conveying system integration
- Fitted with sack rest table
- Dust tight design, non-vibratory
- Low maintenance/running costs
- Mobile support frame

TYPICAL MATERIALS

- Compacted dried fruits
- Biscuits for cheese cake bases
- Powder compacted by storage or conveying
- Agglomerated powders
- Fudge blocks
- Meringue
- Honeycomb

PRODUCT OPTIONS

Machine configurations*

- Deagglomeration of product (lump breaking)
- ATEX upgrade
- Wedgewire mesh basket
- Bonded mesh basket
- Sacktip type infeed

- Fines transition piece
- Oversize transition piece
- Oversize collection barrel
- Fill level alarm
- Oversize outlet control

Finishes available

- Mirror polish to internal stainless parts (standard < 0.8Ra)
- Dressing of all internal/external welds - all stainless parts
- Pharmaceutical mirror polish < 0.25Ra & dressing of all external welds
- Passivation after polish to all stainless parts
- Vivateq/Sublimotion finish to all stainless parts
- Electropolish to all stainless parts

CERTIFIED TECHNOLOGY



*More options available on request

Rota Range

SM R350-ST & R350-ST-LB

Centrifugal Check Sifter with Fixed Drive Shaft Supported at Both Ends

The R350-ST is the large capacity model of the Sievmaster Rota Series. The mesh baskets have a larger diameter and are slightly longer than those used on the R200 sieves. The auger also moves a much larger volume of product per revolution due to the increase in diameter. The R350-ST-LB comes with the addition of a larger sized inlet measuring 430 x 880mm, extending the auger by 450mm. The purpose of this is to improve the ability of the auger to handle product that's more difficult to break down.



INDUSTRIES



Food & Drink



Pharmaceutical



Chemical



Nutraceutical



Reclamation & Recycling



Additive Manufacturing

FEATURES

- Inlets and outlets are designed with standardised flanges but can be supplied with adaptors to suit any connection
- All motors and electrical items are IP55 rated, machine can be washed down without fear of ingress
- All doors and access points are fitted with magnetic interlock switches
- Pneumatic conveying system integration

- Dust tight design, non-vibratory
- Low maintenance/running costs
- Quick change screens with an easy clean design
- Constructed from FDA compliant materials and without crevices

TYPICAL MATERIALS

- Spices
- Cosmetics
- Seeds
- Liquid separation
- Most non-friable powders/granular products
- Flour
- Crystal sugar
- Starch
- Cocoa
- Agrochemicals/fertiliser

PRODUCT OPTIONS

Machine configurations*


- Deagglomeration of product (lump breaking)




- ATEX upgrade



- Wedgewire mesh basket



- Inlet transition piece



- Fines transition piece



- Oversize transition piece



- Easy clean magnet assy to fines



- Support frame - static/mobile



- Oversize collection barrel



- Fill level alarm



- Oversize outlet control



*More options available on request

Finishes available

- Mirror polish to internal stainless parts (standard < 0.8Ra)
- Dressing of all internal/external welds - all stainless parts
- Pharma mirror polish < 0.25Ra & dressing of all internal/external welds - all stainless parts
- Passivation after polish to all stainless parts
- Viwateq/Sublimation finish to all stainless parts
- Electropolish to all stainless parts

CERTIFIED TECHNOLOGY



Sievmaster Ultrasonic Systems

The integration of Ultrasonic technology into Farleygreene's sieving units has proved to be nothing short of a miraculous solution to not only eliminate mesh de-blinding and blocking, but also to accelerate throughputs by a massive 300% in some cases.

The next generation version goes above and beyond the abilities of its predecessor by applying a continuously varying wave, known as 'frequency variation', to the mesh screen. This solves common problems that the 'single wave' resonance frequency systems of the past suffered from; including heating and 'hot spots' that ran the risk of causing premature mesh failure, as well as the individual tuning of each screen in order to work correctly. The Sievmaster ultrasonic system finds its own frequency and uniformly washes over the entire screen in a smooth and consistent wave pattern; thus reducing the need for wasteful re-meshing. The converter probe is conveniently situated outside the internal sieving area, to escape material caking as well as making the mesh frame much easier to clean. Just a single control box can run 2 screens from one generator box, representing a huge cost saving from other systems on the market, which require the inconvenience of devoting a generator for de-blinding each mesh.




When used with the optional software suite the sonic pulse can be infinitely adjusted to suit the product that is being processed. This software also offers the unique function of up to 6 installed programs for different powders, the program can be pre-set by Farleygreene after testing and can also be saved as a file for you to install remotely. Each program can have 2 pulse variations allowing a sieving mode for a set time followed by a short powerful cleaning mode if required.

Farleygreene can fit the system to all machines from the 'Sievmaster' range of screening equipment, as well as a simple retro fit onto other manufacturer's existing ultrasonic mesh frames. Test units are readily available for demonstration at our facility, or on site trials can also be arranged.

Why ultrasonic screening?


- > Delivers efficient sifting of powders with particle sizes of <300 micron
- > Improves through put up to 300% in some cases
- > Helps to break down agglomerated materials
- > Ensures a long term cleaning/deblinding effect
- > Special attachment for use with laboratory test sieves
- > Software package to allow remote control & analysing



How do ultrasonic screens work?

The generator creates a high frequency signal that the converter changes into an ultrasonic sound wave.


These oscillations are transferred to the mesh screen where they are evenly distributed. The oscillations of the mesh cloth reduce the frictional resistance between the powders and the screen. This reduces the tendency towards blocking and blinding, whilst fluidising the product as it flows across the mesh, resulting in increased throughputs.



After-sales Support

During the life of your Sievmaster machine Farleygreene is here to support you. We provide a fully itemised spares list with exploded numbered drawings for you, bespoke to your machine, once it has been installed, allowing you easy identification of parts when required. We offer parts for a wide range equipment; not only for our own manufactured machinery. We can offer the following:

- > Meshing of new and existing frames and rings, including bespoke items
- > Mesh rolls and panels including woven mesh, perforated, wedge wire and synthetic mesh assemblies
- > Replacement vibratory motors
- > Flexible sleeves & rubber balls
- > Bespoke fabrications



Magnetic assemblies

We can now supply almost any type of magnet you require for your process line. From simple single magnet bars to geared rotating magnet arrays within an enclosed box, suitable for use with powders or liquids.

Our magnets are made from rare earth neodymium and are very stable, giving a very long magnetic life. The magnets can be supplied in a range of strengths, from 7,000 to 11,000 gauss. We can also provide gauss meters to ensure your QA protocols are met time after time.





Some magnets are fitted within the machine itself, but for larger units these are normally setup with external drawer type separators. Our sieving machines can be fitted with rare earth magnetic separators, mainly to stop any ferrous metal entering into production lines post screening.

Process systems & equipment

We have forged relationships with many other process equipment manufacturers, and we can integrate a wide range of items with our sieving machinery. Some of these include:

- > Big bag stations – loading and filling
- > Vacuum and pressure conveyors
- > Mechanical conveyors (flexible, screw, aero types)
- > Weigh platforms
- > Feeders

We can bring all these items together to provide a bespoke system to your application requirements, from design right through to installation.





Choice of mesh

A general guide to our selection

Mesh selection is one of the most important choices when deciding on the sieving machine requirement. Throughput expectations, machine size and style of sieving are controlled by mesh size selection. Influencing factors are given below to aid customers in the choice of mesh for their application.

We provide a full remesh and meshing service for existing rings or frames in either stainless steel 304/316/318LN or 430CS for magnetic detection.

We can remesh to a wide range of standards such as EC1935/2004 & FDA – no matter who the original supplier or manufacturer.

Stainless Steel Mesh

The most common material choice. It provides strength and is resistant to heat. It is ideal where a hot material is to be sieved or where a large amount of product will remain on the screen. It can be supplied in a variety of weave patterns, the most common being a plain grid type weave stainless steel mesh retains its size integrity even on larger meshes.



Magnetic Mesh

Woven mesh can also be supplied in a special 430CS magnetic stainless version, this mesh has a higher chrome content than standard stainless steel mesh. Whilst still corrosion resistant, it can be picked up easily by rare earth magnet assemblies should any breakages occur in use. Another variant is 318LN mesh which is an austenitic-ferritic steel and is highly corrosion resistant but retains its magnetic properties. This type of mesh is available in a very limited range of apertures.



Nylon & Polyester Mesh

Nylon meshes have a smoother filament than stainless steel and are ideal for sieving fine powders. Nylon has inherent abrasion resistance. They are limited to temperatures up to 60°C and will absorb moisture to create a slack and less efficient screen. It can also be coloured RED or BLUE. Polyester is similar to nylon, but superior in that it has a temperature endurance up to 130° C. It is, however, less resistant to abrasion than nylon.



Phosphor Bronze

Often used where explosive materials are sieved, however stainless steel meshes have surpassed phosphor bronze due to availability.



Perforated Mesh

This mesh is made from sheets punched to either square or round apertures. Supplied in sheet form and cut to size, they can be bonded to rings the same as woven mesh. These mesh types are extremely hard wearing and stable in use. They do have a reduced open area so advice should be sought to ensure capacity rates can still be met. Available in most types of stainless steel, aluminium and carbon steel.



Wedgewire Screens

Wedge-wire screens can be fabricated in a range of both flat panels and tubes. Wedge-wire and support profiles are resistance welded with accurate slot dimensions. The screens can be mechanically and electro-polished and given additional surface hardening treatments. Further support structures and fastening brackets, can be added. Tubes can have various end piece connections and additional internal strengthening.




Mesh Service

Most meshes are now a bonded configuration and require a special jig to ensure optimum tension and aperture size integrity – the mesh is stretched along its warp and weft to a precise tension. Hand meshed systems cannot guarantee the size or shape of the aperture due to the stretching of the mesh from differing directions (diamond shaped holes, and irregular hole patterns).

All mesh used by Farleygreene conforms to ISO standards 4782, 4783 and 9044 to ensure quality and accuracy of our meshing service.

Mesh is usually supplied in 1220mm wide rolls and in linear length increments as required. 1020, 1530 & 2000mm wide rolls are available but only in certain apertures.

Farleygreene offer a full re-mesh/meshing service. Please ask for our mesh information charts for more details of mesh apertures available.



Aperture	Mesh	Wire dia	Open area %
0.063	250	0.040	36
0.075	200	0.036	45.7
0.100	165	0.050	44.4
0.150	100	0.100	36
0.200	88	0.090	48
0.250	62	0.160	38
0.400	40	0.220	41
0.500	38	0.160	57.6
0.630	32	0.160	64
0.710	29	0.180	64
0.850	24	0.200	65.5
0.900	23	0.200	67
1.000	19	0.320	57.6
1.250	16.4	0.400	57.6
1.500	12	0.630	49.6
2.000	10	0.560	60
2.500	8.5	0.500	69.4
3.15	6.4	0.800	64
4.000	6.4	0.710	72
5.000	3.6	1.6	57.6
6.300	3.4	1.250	69.4
7.100	3	1.400	69.4
8.000	2.6	1.600	69.4
10.000	2.2	1.400	77
11.200	2	1.600	77
12.500	1.8	1.6	79
16.000	2	2.000	79

$$\text{OPEN AREA (Fo)} = \dots\% \\ \text{Fo} = \frac{A^2}{(A + W)^2} \times 100$$

$$A = \text{APERTURE SIZE} \\ W = \text{WIRE DIAMETER} \\ A + W = \text{PITCH}$$

$$\text{APERTURE SIZE} \times 1000 = \text{MICRONS} \\ \text{MESH COUNT} = \frac{\text{HOLES PER LINEAR INCH}}$$

TABLE SHOWS TYPICAL SIZES ONLY
MANY MORE APERTURES ON REQUEST

Atex Directive

Almost all of our machines conform to the latest ATEX requirements. We can confirm the ratings of each range of our equipment during the design process.

Our technical section at the end of the brochure details which machines are certified for use in explosive atmospheres.

The tables below show some typical zoning and temperature figures.



Zone	A measure of the probability that a hazard may be present		
	1000	100	10
EU IEC GAS	II	II	II
EU IEC DUST	II	II	II
US NEC 500 Gas & Dust	II	II	II

Dust	Categories
Zone 20	Category 1
Zone 21	Category 2
Zone 22	Category 3

T Class	Classification by surface temp
T Class - IEC	Maximum Temperature (°C)
T1	450
T2	300
T3	200
T4	135
T5	100
T6	85

THREE-ANGLE PROJECTION

SM 200-S ARTISAN SIEVE

DIMENSION	SM200-S (mm)
A	565
B	300
C	250
D	150

SCREEN DIAMETER = 200mm
BENCH MOUNT LEGS GIVE OUTLET HEIGHT @ 355mm FROM GROUND

ELECTRICAL	SM200-S
VOLTAGE	110 / 240
FREQUENCY	50 / 60 Hz
POWER	45 W
PHASE	1
ATEX	NO

ALL DIMS. AND WEIGHTS ARE TO BE USED FOR DESIGN PURPOSES ONLY. DIMENSIONS ARE TO SURFACE UNLESS OTHERWISE SPECIFIED. © 2022 SIEVE MASTER LTD. ALL RIGHTS RESERVED. ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

THREE-ANGLE PROJECTION

SM E-400-GRV & STV

DIMENSION (mm)	A	B	C	D
SM E-400-GRV	735	840	1028	100
SM E-400-STV	735	840	1110	400

FOR UNDERSCREEN MAGNET, ADD 55 TO DIMENSION

ELECTRICAL	SM E-400
VOLTAGE	110-240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	3 Phase 0.17kW / 0.17kW
PHASE	1 / 3
ATEX	YES

ALL DIMS. AND WEIGHTS ARE TO BE USED FOR DESIGN PURPOSES ONLY. DIMENSIONS ARE TO SURFACE UNLESS OTHERWISE SPECIFIED. © 2022 SIEVE MASTER LTD. ALL RIGHTS RESERVED. ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

THREE-ANGLE PROJECTION

SM 500-S

DIMENSION	SM500-S (mm)
A	800
B	800
C	500
D	300
E	450
F	750

SCREEN DIAMETER = 400mm
BESPOKE FRAMES AVAILABLE WITH DOL BOX, CABLE & PLUG

ELECTRICAL	SM500-S
VOLTAGE	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	85 W
PHASE	1 / 3
ATEX	YES ☹️

ALL DIMS. AND WEIGHTS ARE TO BE USED FOR DESIGN PURPOSES ONLY. DIMENSIONS ARE TO SURFACE UNLESS OTHERWISE SPECIFIED. © 2022 SIEVE MASTER LTD. ALL RIGHTS RESERVED. ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

THREE-ANGLE PROJECTION

SM SLIMLINE 550-FF & 950-ST

DIMENSION	SM550-FF (mm)	SM950-ST (mm)
A	510	755
B	415	665
C	100 (OPTIONAL)	150 (OPTIONAL)
D	150 - 530	150 - 900
E	100 (OPTIONAL)	100/150 (OPTIONAL)
F	150 - 300	150 - 400
G	400 *	485

SCREEN DIAMETER = 565mm & 965mm
BESPOKE FRAMES AVAILABLE - BFM/JACOBS ENDS CAN BE FITTED
*FOR SM550-FF WITH UNDERSCREEN MAGNET ASSY ADD 50mm TO 'G' DIM
ALLOW min. 50mm FOR FLEXIBLE CONNECTIONS TO INLET/OUTLET

ELECTRICAL	SM550-FF	SM950-ST
VOLTAGE	110 / 240 / 380-460	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz	50 / 60 Hz
POWER	0.3 kW	0.9 kW
PHASE	1 / 3	1 / 3
ATEX	YES ☹️	YES ☹️

FOR SM550-FF OPEN TOP GALILEY REFER TO SM700-ST DRAWING

ALL DIMS. AND WEIGHTS ARE TO BE USED FOR DESIGN PURPOSES ONLY. DIMENSIONS ARE TO SURFACE UNLESS OTHERWISE SPECIFIED. © 2022 SIEVE MASTER LTD. ALL RIGHTS RESERVED. ALL DATA SUBJECT TO CHANGE WITHOUT NOTICE.

3-DIMENSIONAL PROJECTION

SM SLIMLINE 1250-ST & 1550-ST

DIMENSION	SM1250-ST (mm)	SM1550-ST (mm)
A	842	1000
B	750	950
C	150 - 900	150 - 900
D	150 (OPTIONAL)	150 (OPTIONAL)
E	150 - 600	150 - 600
F	685	1010

SCREEN DIAMETER = 1165mm & 1465mm
 BESPOKE FRAMES AVAILABLE - BFM/JACOB ENDS CAN BE FITTED
 ALLOW min. 50mm FOR FLEXIBLE CONNECTIONS TO INLET/OUTLET

ELECTRICAL	SM1250-ST	SM1550-ST
VOLTAGE	110 / 240 / 380-460	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz	50 / 60 Hz
POWER	0.9 kW	1.1 kW
PHASE	1 / 3	1 / 3
ATEX	YES	YES

ALL DIM. AND WEIGHTS ARE TO BE USED FOR FINAL PLANNING ONLY. DIMENSIONS CAN BE IN ACCORDANCE WITH ISO STANDARDS AT ANY TIME.

3-DIMENSIONAL PROJECTION

SM SLIMLINE 950 VS/PS

DIMENSION	SM 950 VS/PS
A	DN75 DN1367A
B	1106
C	260
D	DN75 DN1367A
E	250
F	431
G	1340
H	750
I	621
J	753
K	660

SCREEN DIAMETER = 965
 FRAMES FOR SM950 DIFFER FROM UNIT SHOWN - FOR GUIDANCE ONLY
 HOSE CONNECTIONS CAN BE MADE TO MATCH LINE

ELECTRICAL	SM 950 VS/PS
VOLTAGE	110-240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	0.35 kW
PHASE	1 / 3
ATEX	YES

ALL DIM. AND WEIGHTS ARE TO BE USED FOR FINAL PLANNING ONLY. DIMENSIONS CAN BE IN ACCORDANCE WITH ISO STANDARDS AT ANY TIME.

3-DIMENSIONAL PROJECTION

SM SLIMLINE 550, 950 & 1250 VS/PS

DIMENSION	SM 550 VS/PS
A	DN 50 DIN32676
B	1205
C	350
D	DN50 DIN32676
E	307
F	646
G	1300
H	765
I	388
J	508
K	846

ELECTRICAL	SM 550 VS/PS
VOLTAGE	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	0.3 kW
PHASE	1 / 3
ATEX	YES

SCREEN DIAMETER = 565
 *HOSE CONNECTIONS CAN BE MADE TO MATCH LINE

ALL DIM. AND WEIGHTS ARE TO BE USED FOR FINAL PLANNING ONLY. DIMENSIONS CAN BE IN ACCORDANCE WITH ISO STANDARDS AT ANY TIME.

3-DIMENSIONAL PROJECTION

SM SLIMLINE 1250 VS/PS

DIMENSION	SM 1250 VS/PS
A	DN100 DIN32676
B	1293
C	627
D	DN100 DIN32676
E	250
F	526
G	1492
H	930
I	756
J	836
K	844

SCREEN DIAMETER = 1165mm
 FRAMES FOR 1250 DIFFER FROM UNIT SHOWN - FOR GUIDANCE ONLY
 HOSE CONNECTIONS CAN BE MADE TO MATCH LINE

ELECTRICAL	SM 1250 VS/PS
VOLTAGE	110-240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	1.1 kW
PHASE	3
ATEX	YES

ALL DIM. AND WEIGHTS ARE TO BE USED FOR FINAL PLANNING ONLY. DIMENSIONS CAN BE IN ACCORDANCE WITH ISO STANDARDS AT ANY TIME.

SM EASILIFT 550 & 950

DIMENSION	SM-E5L-550 (mm)	SM-E5L-950 (mm)
A	1050	1300
B	1000	1250
C	150	150
D	150 - 300*	150 - 400*
E	610	610
F	510	632
G	300 - 1000*	300 - 1000*
H	900	1100

SCREEN DIAMETER = 565mm & 965mm
 **FOR OUTLET HEIGHTS OVER 450/300mm STEP MAY BE REQUIRED
 *AVAILABLE WITH OUTLET SUITABLE FOR CONNECTION TO VACUUM LINE

ELECTRICAL	SM-E5L-550	SM-E5L-950
VOLTAGE	110 / 240 / 380-460	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz	50 / 60 Hz
POWER	0.3 kW	0.9 kW
PHASE	1 / 3	1 / 3
ATEX	YES	YES

SM MULTISCREEN 800, 1200, 1500

DIMENSION (mm)	800	1200	1500
SM800-P2	800	1100	1500
SM800-P3	800	1100	1500
SM800-P4	800	1100	1500
SM1200-P2	1170	1690	2500
SM1200-P3	1170	1690	2500
SM1200-P4	1170	1690	2500
SM1500-P2	1470	1820	2500
SM1500-P3	1470	1820	2500
SM1500-P4	1470	1820	2500

SCREEN DIAMETER = REFER TO 'A' DIM
 FLEXIBLE CONNECTIONS TO INLET & OUTLETS - MOBILE VERSION AVAILABLE

ELECTRICAL	SM800	SM1200	SM1500
VOLTAGE	110 / 240 / 380-460	110 / 240 / 380-460	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
POWER	0.53 / 0.67 kW	0.90 / 1.05 kW	2.15 / 2.70 kW
PHASE	3	3	3
ATEX	YES	YES	YES

SM EASILIFT 550 ULTRA

DIMENSION	SM-E5L-550-UL
A	1050
B	250
C	1500
D	600
E	1000 - 1000
F	150 - 300
G	900
H	1000
I	500
J	1100

SCREEN DIAMETER = 565mm
 **FOR OUTLET HEIGHTS OVER 450/300mm STEP MAY BE REQUIRED
 *AVAILABLE WITH OUTLET SUITABLE FOR CONNECTION TO VACUUM LINE

ELECTRICAL	SM-E5L-550-UL
VOLTAGE	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	0.3 kW
PHASE	1 / 3
ATEX	YES

SM 700-ST

DIMENSION	SM700-ST (mm)
A	430
B	630
C	530
D	350*
E	100
F	770

SCREEN DIAMETER = 565mm
 ENCLOSED TOP & OVERSIZE OUTLET AVAILABLE (REFER TO SM550-FF DRG)
 *FOR UNDERSCREEN MAGNET ASSY ADD 50mm TO 'D' DIM
 ALLOW min. 50mm FOR FLEXIBLE CONNECTIONS TO INLET/OUTLET

ELECTRICAL	SM700-ST
VOLTAGE	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	0.55 kW
PHASE	1 / 3
ATEX	YES

THREE-ANGLE RESOLUTION

SM SEGREGATOR 42 & 53

DIMENSION	SM SEG 42 (mm)	SM SEG 53 (mm)
A	1550	1850
B	1160	1490
C	600	900
D	555	555
E	165	165
F	500	500

SCREEN SIZE = 1245 x 645mm & 1540 x 915mm
 FOR ADDITIONAL DECKS ADD 180mm PER EXTRA SCREEN
 BESPOKE FRAMES AVAILABLE - MOBILE OR STATIC
 INLET & OUTLETS CONFIGURED TO SUIT INSTALLATION - TYPICAL VERSION SHOWN

ELECTRICAL	SM SEG 42	SM SEG 53
VOLTAGE	110 / 240 / 380-460	110 / 240 / 380-460
FREQUENCY	50 / 60 Hz	50 / 60 Hz
POWER	0.55 kW x 2	0.55 kW x 2
PHASE	3	3
ATEX	YES	YES

TYPICAL VERSION SHOWN - UNIT CAN BE OPEN OR ENCLOSED

THREE-ANGLE RESOLUTION

SM R200-C

DIMENSION	R200-C
A	1054
B	552
C	480
D	715
E	480
F	180
G	1710

SCREEN SIZE = 790mm x Ø200mm LONG
 BESPOKE FRAMES AVAILABLE - MOBILE OR STATIC
 SUITABLE FOR USE WITH VACUUM OR PRESSURE LINES
 OUTLET HOPPER CAN BE SUPPLIED TO SUIT INSTALLATION

ELECTRICAL	R200-C
VOLTAGE	240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	2.2 kW
PHASE	3
ATEX	YES

THREE-ANGLE RESOLUTION

SM R200-ST & R200-ST-LB

DIMENSION	R200	R200-LB
A	1380	1380
B	428	678
C	473	472
D	420	420
E	474	474
F	1815	1783
G	200	070
H	200	280

SCREEN SIZE = 790mm x Ø200mm LONG
 BESPOKE FRAMES AVAILABLE - MOBILE OR STATIC
 SUITABLE FOR USE WITH VACUUM OR PRESSURE LINES
 OUTLET HOPPER CAN BE SUPPLIED TO SUIT INSTALLATION

ELECTRICAL	R200-ST & R200-LB
VOLTAGE	240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	2.2kW (ST) 3.0kW (LB)
PHASE	3
ATEX	YES

THREE-ANGLE RESOLUTION

SM R200-DISINTEGRATOR

DIMENSION	DISINTEGRATOR
A	2270
B	1300
C	910
D	910
E	910
F	910
G	1400
H	1400
I	1400
J	1400
K	1400
L	1400
M	1400
N	1400
O	1400
P	1400
Q	1400
R	1400
S	1400
T	1400
U	1400
V	1400
W	1400
X	1400
Y	1400
Z	1400

SCREEN SIZE = 790mm x Ø200mm LONG
 BESPOKE FRAMES AVAILABLE - MOBILE OR STATIC
 SUITABLE FOR USE WITH VACUUM OR PRESSURE LINES
 OUTLET HOPPER CAN BE SUPPLIED TO SUIT INSTALLATION

ELECTRICAL	R200-DST
VOLTAGE	240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	3.0 kW
PHASE	3
ATEX	YES

1 2 3 4 5 6

THIS LARGE PICTURE

SM R350-ST & R350-ST-LB

A
B
C
D

DIMENSION		
	R350	R350-LB
A	1327	1327
B	597	1047
C	655	655
D	640	640
E	576	576
F	1924	2374
G	380	830
H	380	380

SCREEN SIZE = 990mm x Ø350mm LONG
 BESPOKE FRAMES AVAILABLE - MOBILE OR STATIC
 SUITABLE FOR USE WITH VACUUM OR PRESSURE LINES
 OUTLET HOPPER CAN BE SUPPLIED TO SUIT INSTALLATION

ELECTRICAL	
R350 & R350-LB	
VOLTAGE	240 / 380-460
FREQUENCY	50 / 60 Hz
POWER	4.0 kW
PHASE	3
ATEX	YES

SM R350-ST & R350-ST-LB



Farleygreene Limited, Unit 2, Hatch Industrial Park, Greywell Road,
Mapledurwell, Hampshire RG24 7NG, United Kingdom

t +44 (0) 1256 474 547
f +44 (0) 1256 329 596
e info@farleygreene.com

farleygreene.com
Company No: 1243329

Distributed by:

Copyright © 2019 Issue A 11.19

